

	Power Source Type	Displacement (cc/cu. in.)	Engine Power (kW/bhp)	Voltage (V)	Weight (lbs)*	Fuel Capacity (oz.)	Standard Cutting Tool	Cutting Swath (in.)	STIHL Easy2Start™ (E)	Anti-vibration System	STIHL M-Tronic™ (M)	Electronic Ignition Module	Multi-function Control Handle	Simplified Starting Procedure	Standard Handle Type	Purge Pump Primer	IntelliCarb™ Compensating Carburetor	Translucent Upright Fuel Tank	Caring for Nature	Made in America
<b>WEEKLY USE AROUND BEDS, DRIVEWAYS, ETC.</b>																				
<b>FS 38</b>		27.2/1.66	0.65/0.87	—	9.3	11.2	AutoCut®	15	—	—	—	●	●	—	Loop	●	—	●	—	
<b>FS 40 C-E</b>		27.2/1.66	0.7/0.94	—	9.9	11.5	AutoCut®	15	●	—	—	●	●	●	Loop	●	—	●		
<b>FSA 45</b>		—	—	18	5.1	—	STIHL PolyCut™	9	—	—	—	—	—	—	Loop	—	—	—		
<b>FS 50 C-E</b>		27.2/1.66	0.8/1.07	—	10.1	11.5	AutoCut®	16.5	●	—	—	●	●	●	Loop	●	—	●		
<b>FS 56 C-E</b>		27.2/1.66	0.8/1.07	—	11.5	11.5	AutoCut®	16.5	●	—	—	●	●	●	Bike	●	—	●		
<b>FS 56 RC-E</b>		27.2/1.66	0.8/1.07	—	10.6	11.5	AutoCut®	16.5	●	—	—	●	●	●	Loop	●	—	●		
<b>FSA 57</b>		—	—	36	5.95	—	AutoCut®	11	—	—	—	—	—	—	Loop	—	—	—		
<b>FSA 60 R</b>		—	—	36	7.1	—	AutoCut®	13.8	—	—	—	—	—	—	Loop	—	—	—		
<b>FSE 60</b>		—	—	120	8.8	—	AutoCut®	14	—	—	—	—	—	—	Loop	—	—	—		
<b>LARGE YARDS, LONGER FENCE LINES</b>																				
<b>FS 70 R</b>		27.2/1.66	0.9/1.2	—	10.6	11.5	AutoCut®	16.5	—	—	—	●	●	●	Loop	●	—	●		
<b>FSA 86 R</b>		—	—	36	7.3	—	AutoCut®	13.8	—	—	—	—	—	—	Loop	—	—	—		
<b>FSA 90 R</b>		—	—	36	6.2	—	AutoCut®	15	—	—	—	—	—	—	Loop	—	—	—		
<b>FS 91</b>		28.4/1.73	0.95/1.27	—	12.8	24.0	AutoCut®	16.5	—	●	—	●	●	●	Bike	●	●	●		
<b>FS 91 R</b>		28.4/1.73	0.95/1.27	—	12.1	24.0	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
<b>FS 94 R</b>		24.1/1.47	0.9/1.2	—	10.1	18.3	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	—	●		
<b>FS 111 RX</b>		31.4/1.9	1.05/1.4	—	11.0	24.0	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
<b>PROFESSIONAL JOBS, EXTENDED TRIMMING TIMES</b>																				
<b>FS 111</b>		31.4/1.9	1.05/1.4	—	12.8	24.0	AutoCut®	16.5	—	●	—	●	●	●	Bike	●	●	●		
<b>FS 111 R</b>		31.4/1.9	1.05/1.4	—	12.1	24.0	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
<b>FS 131</b>		36.3/2.2	1.4/1.9	—	12.8	24.0	AutoCut®	16.5	—	●	—	●	●	●	Bike	●	●	●		
<b>FS 131 R</b>		36.3/2.2	1.4/1.9	—	12.1	24.0	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
<b>FSA 135</b>		—	—	36	10.8	—	AutoCut®	16.5	—	—	—	—	—	—	Bike	—	—	—		
<b>FSA 135 R</b>		—	—	36	10.1	—	AutoCut®	16.5	—	—	—	—	—	—	Loop	—	—	—		
<b>FS 240</b>		37.7/2.3	1.7/2.3	—	15.2	25.4	AutoCut®	16.5	—	●	—	●	●	●	Bike	●	●	●		
<b>FS 240 R</b>		37.7/2.3	1.7/2.3	—	14.6	25.4	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
<b>FS 311</b>		36.3/2.2	1.4/1.9	—	15.9	24.0	AutoCut®	18.9	—	●	—	●	●	●	Bike	●	●	●		
<b>FS 361 C-EM</b>		37.7/2.3	1.7/2.3	—	19.18	25.4	N/A	20.5	●	●	●	●	●	●	Bike	●	●	●		
<b>FS 461 C-EM</b>		45.6/2.8	2.2/3.0	—	19.22	25.4	N/A	20.5	●	●	●	●	●	●	Bike	●	●	●		
<b>FS 561 C-EM</b>		57.1/3.48	2.8/3.75	—	22.5	33.5	N/A	22	●	●	●	●	●	●	Bike	●	●	●		

● Standard    ○ Optional    — Not Applicable

\*Dry weight without cutting attachment or deflector.

Note: Specifications are as of Oct. 1, 2022. For most recent updates, visit [STIHLusa.com](http://STIHLusa.com). Models and specifications are subject to change without notice.

Manufacturer reserves the right to change appearance, function and components of any STIHL product without prior notice or liability.

Note: STIHL trimmers and brushcutters are designed to work with a variety of cutting attachments.

