

STIHL TRIMMERS & BRUSHCUTTERS

	Power Source Type	Displacement (cc/cu. in.)	Engine Power (kW/bhp)	Voltage (V)	Weight (lbs.)*	Fuel Capacity (oz.)	Standard Cutting Tool	Cutting Swath (in.)	STIHL Easy2Start™ (E)	Anti-vibration System	STIHL M-Tronic™ (M)	Electronic Ignition Module	Multi-function Control Handle	Simplified Starting Procedure	Standard Handle Type	Purge Pump Primer	IntelliCarb™ Compensating Carburetor	Translucent Upright Fuel Tank	Caring for Nature	Made in America®
WEEKLY USE AROUND BEDS, DRIVEWAYS, ETC.																				
FS 38		27.2/1.66	0.65/0.87	—	9.3	11.2	AutoCut®	15	—	—	—	●	●	—	Loop	●	—	●	—	—
FS 40 C-E		27.2/1.66	0.7/0.94	—	9.9	11.5	AutoCut®	15	●	—	—	●	●	●	Loop	●	—	●		
FSA 45		—	—	18	5.1	—	STIHL PolyCut™	9	—	—	—	—	—	—	Loop	—	—	—		—
FS 50 C-E		27.2/1.66	0.8/1.07	—	10.1	11.5	AutoCut®	16.5	●	—	—	●	●	●	Loop	●	—	●	—	
FS 56 C-E		27.2/1.66	0.8/1.07	—	11.5	11.5	AutoCut®	16.5	●	—	—	●	●	●	Bike	●	—	●		
FS 56 RC-E		27.2/1.66	0.8/1.07	—	10.6	11.5	AutoCut®	16.5	●	—	—	●	●	●	Loop	●	—	●		
FSA 57		—	—	36	5.95	—	AutoCut®	11	—	—	—	—	—	—	Loop	—	—	—		
FSA 60 R		—	—	36	7.1	—	AutoCut®	13.8	—	—	—	—	—	—	Loop	—	—	—		—
FSE 60		—	—	120	8.8	—	AutoCut®	14	—	—	—	—	—	—	Loop	—	—	—		—
LARGE YARDS, LONGER FENCE LINES																				
FS 70 R		27.2/1.66	0.9/1.2	—	10.6	11.5	AutoCut®	16.5	—	—	—	●	●	●	Loop	●	—	●		
FSA 86 R		—	—	36	7.3	—	AutoCut®	13.8	—	—	—	—	—	—	Loop	—	—	—		—
FSA 90 R		—	—	36	6.2	—	AutoCut®	15	—	—	—	—	—	—	Loop	—	—	—		—
FS 91		28.4/1.73	0.95/1.27	—	12.8	24.0	AutoCut®	16.5	—	●	—	●	●	●	Bike	●	●	●		
FS 91 R		28.4/1.73	0.95/1.27	—	12.1	24.0	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
FS 94 R		24.1/1.47	0.9/1.2	—	10.1	18.3	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	—	●		
FS 111 RX		31.4/1.9	1.05/1.4	—	11.0	24.0	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
PROFESSIONAL JOBS, EXTENDED TRIMMING TIMES																				
FS 111		31.4/1.9	1.05/1.4	—	12.8	24.0	AutoCut®	16.5	—	●	—	●	●	●	Bike	●	●	●		
FS 111 R		31.4/1.9	1.05/1.4	—	12.1	24.0	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
FS 131		36.3/2.2	1.4/1.9	—	12.8	24.0	AutoCut®	16.5	—	●	—	●	●	●	Bike	●	●	●		
FS 131 R		36.3/2.2	1.4/1.9	—	12.1	24.0	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		
FSA 135		—	—	36	10.8	—	AutoCut®	16.5	—	—	—	—	—	—	Bike	—	—	—		—
FSA 135 R		—	—	36	10.1	—	AutoCut®	16.5	—	—	—	—	—	—	Loop	—	—	—		—
FS 240		37.7/2.3	1.7/2.3	—	15.2	25.4	AutoCut®	16.5	—	●	—	●	●	●	Bike	●	●	●		—
FS 240 R		37.7/2.3	1.7/2.3	—	14.6	25.4	AutoCut®	16.5	—	●	—	●	●	●	Loop	●	●	●		—
FS 311		36.3/2.2	1.4/1.9	—	15.9	24.0	AutoCut®	18.9	—	●	—	●	●	●	Bike	●	●	●		—
FS 361 C-EM		37.7/2.3	1.7/2.3	—	19.18	25.4	N/A	20.5	●	●	●	●	●	●	Bike	●	●	●	—	—
FS 461 C-EM		45.6/2.8	2.2/3.0	—	19.22	25.4	N/A	20.5	●	●	●	●	●	●	Bike	●	●	●	—	—
FS 561 C-EM		57.1/3.48	2.8/3.75	—	22.5	33.5	N/A	22	●	●	●	●	●	●	Bike	●	●	●	—	—

● Standard ○ Optional — Not Applicable
 *Dry weight without cutting attachment or deflector.

Note: Specifications are as of Oct. 1, 2022. For most recent updates, visit STIHLusa.com. Models and specifications are subject to change without notice. Manufacturer reserves the right to change appearance, function and components of any STIHL product without prior notice or liability.

Note: STIHL trimmers and brushcutters are designed to work with a variety of cutting attachments.

*Made in America of U.S. and global materials. Batteries and chargers sourced internationally.