

# RZ



## HOMEOWNER MODELS



STIHL RZ 142 MOWER



STIHL RZ 152 MOWER



STIHL RZ 261 MOWER



STIHL RZ 500 SERIES



STIHL RZ 700 SERIES



STIHL RZ 900 SERIES

ZERO-TURN MOWERS	ENGINE										DECK						SUSPENSION				SEAT		FEATURES						TIRES		Weight (lbs)	Made in America of U.S. and global materials*														
	Power Source Type	Briggs & Stratton® Professional V-twin	Briggs & Stratton® Commercial V-twin	Briggs & Stratton® Commercial V-twin (461877)	Varicharge® EFI (49E877) w/ Oil Guard (01G2)	Varicharge® EFI (49E877) w/ Oil Guard (01G2)	Kawasaki FT730V	Kawasaki FX801V	Kawasaki FX1000V EFI	Kawasaki FX1000V-EFI	Engine Displacement	Engine Horsepower (hp)	Gasoline Volume (gal)	Hydro-Gear® Transaxle Model	Top Speed Forward (mph)	Top Speed Reverse (mph)	Mowing Deck Size (in)	Mowing Height Range (in)	Blades	Cutting Height Options	Mowing Height Adjustment	Fabricated Mowing Deck	Mowing Deck Side Discharge	Spindle Size (in)	Mowing Spindle Type	Pivoting Axle w/ Shocks	Independent Front End Suspension w/ Shocks	Rear Suspension System With Shocks	Mower Height Follows Suspension Movement	Seat Suspension			Seat Back Height	Seat Armrests	Seat Belt	Roll Over Protection System (ROPS) - Foldable	LED Headlight	Dual USB-A 2.0 (3.1A Amps) Charger	Cupholder (2)	STIHL connected Fleet Management/Connectivity Hour Meter	Fuel Level Indicator	Front Caster	Rear Tire			
STIHL RZ 142	●	-	-	-	-	-	-	-	-	724	23	≥ 3	ZT-2200	≈ 7	≈ 4	42	1.5-4.5	2	13	Manual	●	●	n/a	Aluminum	-	-	-	-	-	"Medium" #15"	○	-	-	○	○	○	○	○	○	○	Sight Level	11 x 6-5	20 x 8-8	563	USA	
STIHL RZ 152	●	-	-	-	-	-	-	-	-	724	25	≥ 3	ZT-2800	≈ 8	≈ 4	52	1.5-4.5	3	13	Manual (Spring)	●	●	n/a	Aluminum	●	-	●	-	-	"Medium" #15"	○	-	-	○	●	●	○	●	○	●	Fuel Gauge	11 x 6-5	22 x 10-10	732	USA	
STIHL RZ 261	●	-	●	-	-	-	-	-	-	724	25	≥ 3	ZT-3100	≈ 8.5	≈ 4	61	1.5-4.5	3	13	Manual (Spring)	●	●	n/a	Aluminum	●	-	●	-	-	"Medium" #18"	○	-	-	○	●	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	22 x 11-10	965	USA	
STIHL RZ 552	●	-	-	●	-	-	-	-	-	810	27	≥ 5.5	ZT-3400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	●	●	5.25	Aluminum	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	23 x 10.5-12	1,119	USA
STIHL RZ 552 K	●	-	-	-	-	-	-	-	-	726	24	≥ 5.5	ZT-3400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	●	●	5.25	Aluminum	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	23 x 10.5-12	1,119	USA
STIHL RZ 560	●	-	-	-	-	-	-	-	-	810	27	≥ 5.5	ZT-3400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	●	●	5.25	Aluminum	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	23 x 10.5-12	1,197	USA
STIHL RZ 560 K	●	-	-	-	-	-	-	-	-	726	24	≥ 5.5	ZT-3400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	●	●	5.25	Aluminum	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	23 x 10.5-12	1,197	USA
STIHL RZ 752i	●	-	-	-	●	-	-	-	-	810	28	≥ 11	ZT-4400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	●	●	79	Cast iron	-	●	●	●	-	"High" #18"	○	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	24 x 9.5-12	1,319	USA
STIHL RZ 752 K	●	-	-	-	-	-	-	-	-	726	25.5	≥ 11	ZT-4400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	●	●	79	Cast iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	24 x 9.5-12	1,319	USA
STIHL RZ 752i K	●	-	-	-	-	-	-	-	-	726	26	≥ 11	ZT-4400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	●	●	79	Cast iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	24 x 9.5-12	1,319	USA
STIHL RZ 760i	●	-	-	-	-	-	-	-	-	810	28	≥ 11	ZT-4400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	●	●	79	Cast iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	24 x 12-12	1,398	USA
STIHL RZ 760 K	●	-	-	-	-	-	-	-	-	726	25.5	≥ 11	ZT-4400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	●	●	79	Cast iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	24 x 12-12	1,398	USA
STIHL RZ 760i K	●	-	-	-	-	-	-	-	-	726	26	≥ 11	ZT-4400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	●	●	79	Cast iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	24 x 12-12	1,398	USA
STIHL RZ 960i	●	-	-	-	-	●	-	-	-	993	40	≥ 11	ZT-5400	≈ 12	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	●	●	10	Cast iron	-	●	●	●	-	"Extra High"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,608	USA
STIHL RZ 960 K	●	-	-	-	-	-	-	-	-	999	35	≥ 11	ZT-5400	≈ 12	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	●	●	10	Cast iron	-	●	●	●	-	"Extra High"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,608	USA
STIHL RZ 960i K	●	-	-	-	-	-	-	-	-	999	38.5	≥ 11	ZT-5400	≈ 12	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	●	●	10	Cast iron	-	●	●	●	-	"Extra High"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,608	USA
STIHL RZ 972i	●	-	-	-	-	●	-	-	-	993	40	≥ 11	ZT-5400	≈ 12	≈ 5	72	1.5-5.0	3	13	Manual (Spring)	●	●	10	Cast iron	-	●	●	●	-	"Extra High"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,717	USA
STIHL RZ 972 K	●	-	-	-	-	-	-	-	-	999	35	≥ 11	ZT-5400	≈ 12	≈ 5	72	1.5-5.0	3	13	Manual (Spring)	●	●	10	Cast iron	-	●	●	●	-	"Extra High"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,717	USA
STIHL RZ 972i K	●	-	-	-	-	-	-	-	-	999	38.5	≥ 11	ZT-5400	≈ 12	≈ 5	72	1.5-5.0	3	13	Manual (Spring)	●	●	10	Cast iron	-	●	●	●	-	"Extra High"	●	●	●	●	●	○	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,717	USA

\*Made in America of U.S. and global materials. Attachments and accessories sourced internationally.

● Standard ○ Optional - Not Applicable