

GAS-POWERED ZERO-TURN MOWERS

STIHL

HOMEOWNER MODELS



STIHL RZ 142 MOWER



STIHL RZ 152 MOWER



STIHL RZ 261 MOWER

PROFESSIONAL MODELS



STIHL RZ 500 SERIES



STIHL RZ 700 SERIES



STIHL RZ 900 SERIES

ZERO-TURN MOWERS	ENGINE TYPE	DECK										SUSPENSION				SEAT		FEATURES						TIRES		Weight (lbs.)	Made in America °									
		Engine Displacement (cc)	Engine Horsepower (hp)	Gasoline Volume (gal.)	Hydro-Gear® Transaxle Model	Top Speed Forward (mph)	Top Speed Reverse (mph)	Mowing Deck Size (in.)	Mowing Height Range (in.)	MARBAIN® Hardened Blades	Cutting Height Options	Mowing Height Adjustment	Fabricated Mowing Deck	Mowing Deck Side Discharge	Spindle Size (in.)	Spindle Type	Pivoting Axle w/ Shocks	Independent Front End Suspension w/ Shocks	Rear Suspension System w/ Shocks	Lower Height Follows Suspension Movement	Seat Suspension	Seat Back Height	Seat Armrests	Seat Belt	Foldable Roll Over Protection System (ROPS)			LED Headlight	Dual USB-A 2.0 (3.1A Amps) Charger	Cupholder (2)	STIHL connected Fleet Management/Connectivity Hour Meter	Fuel Level Indicator	Front Caster	Rear Tire		
STIHL RZ 142	Briggs & Stratton® Professional V-Twin	724	23	≥ 3	ZT-2200	≈ 7	≈ 4	42	1.5-4.5	2	13	Manual	● ●	n/a	Aluminum	-	-	-	-	-	"Medium" #15"	○	-	-	○	○	○	○	○	○	○	Sight Level	11 x 6-5	20 x 8-8	563	
STIHL RZ 152	Briggs & Stratton® Professional V-Twin	724	25	≥ 3	ZT-2800	≈ 8	≈ 4	52	1.5-4.5	3	13	Manual (Spring)	● ●	n/a	Aluminum	●	-	●	-	-	"Medium" #15"	○	-	-	○	●	●	○	●	○	●	Fuel Gauge	11 x 6-5	22 x 10-10	732	
STIHL RZ 261	Briggs & Stratton® Commercial V-Twin	724	25	≥ 3	ZT-3100	≈ 8.5	≈ 4	61	1.5-4.5	3	13	Manual (Spring)	● ●	n/a	Aluminum	●	-	●	-	-	"High" #18"	○	-	-	○	●	●	○	●	○	●	Fuel Gauge	13 x 6.5-6	22 x 11-10	815	
STIHL RZ 552	Briggs & Stratton® Commercial (48T877)	810	27	≥ 5.5	ZT-3400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	● ●	5.25	Aluminum	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	23 x 10.5-12	1,232	
STIHL RZ 552 K	Kawasaki FT730V	726	24	≥ 5.5	ZT-3400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	● ●	5.25	Aluminum	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	23 x 10.5-12	1,249	
STIHL RZ 560	Briggs & Stratton® Commercial (48T877)	810	27	≥ 5.5	ZT-3400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	● ●	5.25	Aluminum	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	23 x 10.5-12	1,277	
STIHL RZ 560 K	Kawasaki FT730V	726	24	≥ 5.5	ZT-3400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	● ●	5.25	Aluminum	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	23 x 10.5-12	1,291	
STIHL RZ 752i	Vanguard® EFI w/ Oil Guard™ (49E877)	810	28	≥ 11	ZT-4400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	● ●	79	Cast Iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	24 x 9.5-12	1,319	
STIHL RZ 752 K	Kawasaki FX801V	852	25.5	≥ 11	ZT-4400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	● ●	79	Cast Iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	24 x 9.5-12	1,316	
STIHL RZ 752i K	Kawasaki FT730V EFI	726	26	≥ 11	ZT-4400	≈ 10	≈ 5	52	1.5-5.0	3	13	Manual (Spring)	● ●	79	Cast Iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	24 x 9.5-12	1,298	
STIHL RZ 760i	Vanguard® EFI w/ Oil Guard™ (49E877)	810	28	≥ 11	ZT-4400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	● ●	79	Cast Iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	24 x 12-12	1,406	
STIHL RZ 760 K	Kawasaki FX801V	852	25.5	≥ 11	ZT-4400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	● ●	79	Cast Iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	24 x 12-12	1,402	
STIHL RZ 760i K	Kawasaki FT730V EFI	726	26	≥ 11	ZT-4400	≈ 10	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	● ●	79	Cast Iron	-	●	●	●	-	"High" #18"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	24 x 12-12	1,389	
STIHL RZ 960i	Vanguard® BIG BLOCK EFI ETC w/ Oil Guard™ (61G2)	993	40	≥ 11	ZT-5400	≈ 12	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	● ●	10	Cast Iron	-	●	●	●	●	"Extra High"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,631	
STIHL RZ 960 K	Kawasaki FX1000V	999	35	≥ 11	ZT-5400	≈ 12	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	● ●	10	Cast Iron	-	●	●	●	●	"Extra High"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,621	
STIHL RZ 960i K	Kawasaki FX1000V-EFI	999	38.5	≥ 11	ZT-5400	≈ 12	≈ 5	60	1.5-5.0	3	13	Manual (Spring)	● ●	10	Cast Iron	-	●	●	●	●	"Extra High"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,640	
STIHL RZ 972i	Vanguard® BIG BLOCK EFI ETC w/ Oil Guard™ (61G2)	993	40	≥ 11	ZT-5400	≈ 12	≈ 5	72	1.5-5.0	3	13	Manual (Spring)	● ●	10	Cast Iron	-	●	●	●	●	"Extra High"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,661	
STIHL RZ 972 K	Kawasaki FX1000V	999	35	≥ 11	ZT-5400	≈ 12	≈ 5	72	1.5-5.0	3	13	Manual (Spring)	● ●	10	Cast Iron	-	●	●	●	●	"Extra High"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,653	
STIHL RZ 972i K	Kawasaki FX1000V-EFI	999	38.5	≥ 11	ZT-5400	≈ 12	≈ 5	72	1.5-5.0	3	13	Manual (Spring)	● ●	10	Cast Iron	-	●	●	●	●	"Extra High"	●	●	●	●	●	○	●	○	●	○	Fuel Gauge	13 x 6.5-6	26 x 12-12	1,670	

°STIHL gas-powered zero-turn mowers are made in America of U.S. and global materials. Attachments and accessories sourced internationally.

● Standard ○ Optional - Not Applicable

BATTERY-POWERED ZERO-TURN MOWERS

STIHL



STIHL RZA 748 MOWER



STIHL RZA 752 MOWER



STIHL RZA 760 MOWER

Drive Motor (kw) Blade Motor (kw) Battery Capacity (kWh) Run Time (hrs.) Top Speed Forward (mph) Top Speed Reverse (mph) Mowing Deck Size (in.) Mowing Height Range (in.) MARBAIN® Hardened Blades Cutting Height Options Fabricated Mowing Deck Mowing Deck Side Discharge Seat Suspension Seat Armrests Seat Belt Roll Over Protection System (ROPS) - foldable 360° LED Lights Dual USB-A and USB-C ports Cupholder (2) GPS Connectivity Front Caster Rear Tire Weight (lbs)

BATTERY-POWERED ZERO-TURN MOWERS	MOTORS				DECK				SEAT			FEATURES				TIRES					
NEW! STIHL RZA 748	5	1.8	24	8	≈ 16	≈ 5	42	1.5-4.5	3	17	●	●	●	●	●	●	●	●	13 x 6-5-6	24 x 9.5-12	1,550
NEW! STIHL RZA 752	5	1.8	24	8	≈ 16	≈ 5	52	1.5-4.5	3	17	●	●	●	●	●	●	●	●	13 x 6-5-6	24 x 9.5-12	1,560
NEW! STIHL RZA 760	5	1.8	24	8	≈ 16	≈ 5	60	1.5-4.5	3	17	●	●	●	●	●	●	●	●	13 x 6-5-6	24 x 9.5-12	1,607