

EDGERS AND BED REDEFINER

	Power Source Type	Displacement (cc/cu. in.)	Mechanical Power Output (kW/bhp)	Weight* (lbs.)	Fuel Capacity (oz.)	Gear Ratio	Maximum Blade Speed (rpm)	Arbor Size (mm/in.)	Blade Size (cm/in.)	Blade Cutting Depth (cm/in.)	Shaft Type Straight/Curved	STIHL Easy2Start™	Adjustable Depth Wheel	"Line of Sight" Marking	"Open" Guard Design	Multi-Function Control Handle	Made in America of U.S. and global materials
EDGERS																	
FC 56 C-E		27.2/1.7	0.8/1.07	13.5	11.5	1:01.0	8,300	25.4/1.0	20.3/8.0	–	Curved	●	●	●	●	●	
FC 70		27.2/1.7	0.9/1.2	13.0	11.5	1:01.2	8,300	25.4/1.0	20.3/8.0	–	Curved	–	●	●	●	●	
FCA 80		–	–	10.8	–	1:01.0	8,300	25.4/1.0	20.3/8.0	–	Curved	–	●	●	●	●	
FC 91		28.4/1.7	1.0/1.3	13.2	24.0	1:01.2	8,100	25.4/1.0	20.3/8.0	–	Curved	–	●	●	●	●	
FC 96		28.4/1.7	1.0/1.3	13.7	24.0	1:02.1	4,800	25.4/1.0	20.3/8.0	–	Straight	–	●	●	●	●	
FC 111		31.4/1.9	1.1/1.4	13.7	24.0	1:02.1	4,800	25.4/1.0	20.3/8.0	–	Straight	–	●	●	●	●	
FCA 135		–	–	11.2	–	1:1.235	8,100	25.4/1.0	20.3/8.0	–	Curved	–	●	●	●	●	
FCA 140		–	–	12.6	–	1:2.09	4,800	25.4/1.0	20.3/8.0	–	Straight	–	●	●	●	●	
BED REDEFINER																	
FB 131		36.3/2.2	1.40/1.90	17.2	24.0	1:02.1	4,800	25.4/1.0	–	6.6/2.6	Straight	–	●	●	●	●	

● Standard – Not Applicable

*Dry weight

Note: Specifications are as of Oct. 1, 2024. For most recent updates, visit [STIHLusa.com](https://www.stihlusa.com). Models and specifications are subject to change without notice. Manufacturer reserves the right to change appearance, function and components of any STIHL product without prior notice.

*Made in America of U.S. and global materials. Batteries and chargers sourced internationally.